



MAX. OUTPUT TORQUE [FT.LB]	MAX. INPUT TORQUE [FT.LB]	RATIO	MECHANICAL ADVANTAGE	THRUST [LB]	WEIGHT [LB]	DRIVE PATTERN [IN]	INPUT SHAFT PATTERN [IN]
1,250	370	3.75:1	3.38	60,000	38	12x3/8-16UNC ON $\phi$ 3.937 B.C	F07

MAX. STEM DIAMETER FOR TORQUE APPLICATION [IN]	MAX. STEM DIAMETER FOR THRUST APPLICATION [IN]	MAX. MOUNTING STRADDLE C/L ON CENTERLINE [IN]	MIN. MOUNTING STRADDLE C/L ON CENTERLINE [IN]	PREFERRED MOUNTING STRADDLE C/L [IN]	PREFERRED MOUNTING ON CENTERLINE [IN]
$\phi$ 3.00	$\phi$ 2.50	$\phi$ 8.50	$\phi$ 6.5	FA16 (STANDARD) FA19 (OPTIONAL)	4x1/2-13UNC $\phi$ 7.63 B.C (STANDARD)



**DIAMOND GEAR CO. LTD.**  
HOUSTON, TEXAS, USA

PHONE: 713-590-0270, FAX: 713-590-0278



C400003A

(D2000)

REV.C

01-14-01