



HANDWHEEL DATA

Ø	RIM PULL AT MAX. OUTPUT TORQUE
12"	147 LBS
14"	126 LBS
16"	111 LBS
18"	98 LBS
20"	88 LBS
24"	74 LBS
30"	59 LBS
36"	49 LBS

MAX. OUTPUT TORQUE [IN.LB]	MAX. INPUT TORQUE [IN.LB]	RATIO	MECHANICAL ADVANTAGE	OUTPUT ANGULAR STROKE	TURN PER 90°	WEIGHT [LB]	PREFERRED ACTUATOR MOUNTING STRADDLE C/L [IN]
43,000	884	216:1	48.6	±5°	54	107	FA10

MAX. ROUND BORE [IN]	MAX. SQUARE BORE [IN]	MAX. MOUNTING STRADDLE C/L [IN]	MIN. MOUNTING STRADDLE C/L [IN]	MAX. MOUNTING ON C/L [IN]	MIN. MOUNTING ON C/L [IN]	PREFERRED VALVE MOUNTING STRADDLE C/L [IN]
Ø3.25 KEY 3/4x1/2	2.50	Ø8.50	Ø6.25	Ø8.50	Ø6.25	FA16 & FA19



DIAMOND GEAR CO. LTD.
HOUSTON, TEXAS, USA

PHONE: 713-590-0270, FAX: 713-590-0278



C400100A

REV.0

01/29/04