



HANDWHEEL DATA

Ø	RIM PULL AT MAX. OUTPUT TORQUE
12"	568 LBS
14"	486 LBS
16"	426 LBS
18"	378 LBS
20"	341 LBS
24"	284 LBS
30"	227 LBS
36"	189 LBS

MAX. OUTPUT TORQUE [IN.LB]	MAX. INPUT TORQUE [IN.LB]	RATIO	MECHANICAL ADVANTAGE	OUTPUT ANGULAR STROKE	TURN PER 90°	WEIGHT [LB]	PREFERRED ACTUATOR MOUNTING STRADDLE C/L [IN]
63,000	3405	74:1	18.5	±5°	18.5	112	FA10 & FA14

MAX. ROUND BORE [IN]	MAX. SQUARE BORE [IN]	MAX. MOUNTING STRADDLE C/L [IN]	MIN. MOUNTING STRADDLE C/L [IN]	MAX. MOUNTING ON C/L [IN]	MIN. MOUNTING ON C/L [IN]	PREFERRED VALVE MOUNTING STRADDLE C/L [IN]
Ø4.0 KEY: 3/4x1	2.812	Ø10.25	Ø7.75	Ø7.75	Ø7.75	FA25



DIAMOND GEAR CO. LTD.
HOUSTON, TEXAS, USA

PHONE: 713-590-0270, FAX: 713-590-0278



C400097A

REV.0

01/29/04